

TECHNICAL DATA SHEETS

PERMOGLAZE ACID CATALYSED VARNISH

DESCRIPTION	Permoglaze Acid Catalysed Varnish is a fast drying two-pack acid curing varnish for industrial wood coating.
CHARACTERISTICS	• Durable
	Transparent
	Highly washable
	Quick drying
	Fast and easy to apply by brush
	Good spreading rate
COMPOSITION	Alkyd/urea formaldehyde resin.
SURFACE	Rub down lightly to ensure a smooth surface. Stain if required.
PREPARATION	 For a superfine finish on open-grained woods, fill the grain and rub with wet or dry abrasive paper
	to a perfectly smooth base.
APPLICATION	Method Air-assisted spray
	Thinning Permoglaze Acid Catalysed Thinner
	Mixing Ratio Base 19
	(By Volume) Catalyst 1
	Cleaning Permoglaze Acid Catalysed Thinner
PRODUCT	Finish Gloss, satin and matt
INFORMATION	Shades Clear
	Spreading Rate 8-10 m²/liter/coat depending on surface porosity, ambient conditions, dilution and application method
	Drying Time Sand Dry ± 15 minutes
	Hard Dry ± 30 minutes
PRECAUTIONS	Seal the end grain of timber to prevent ingress of moisture.
	Do not apply to wet or damp timber.
	• Once coating is dry, do not clean or contaminate with alcohol as this will produce a permanent
	residual stain.
PACKAGING	Available in 1, 5 & 20 litres
STORAGE	Keep in a cool, dry place and away from heat sources.

Page 1 of 2

03rd August 2017

Revision 004





TECHNICAL DATA SHEETS

PERMOGLAZE ACID CATALYSED VARNISH

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Flammable. Keep away from sparks, heat and naked flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added Lead/Mercury/Nickel/Cadmium.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.

Page 2 of 2

03rd August 2017

Revision 004



ISO 9001:2015 Certified | ISO 14001:2015 Certified