

TECHNICAL DATA SHEETS

PERMOGLAZE AQUA LASURE

DESCRIPTION	Permoglaze Aqua Lasure is a one-component water-based modified acrylic varnish for all types of wood surfaces.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Eco-friendly • Recommended for interior and exterior use (For exterior, hardwood substrate having a moisture content of less than 10% should be used). • Durable and preserves the natural colour, beauty and grain of the timber • Easy to apply by brush. • Non-yellowing & excellent colour retention • Good spreading rate • Quick drying • Apply directly on bare, dry, clean and sound wood. 	
COMPOSITION	Modified acrylic resin	
SURFACE PREPARATION	<ul style="list-style-type: none"> • The surface must be clean and dry. • The timber must be treated with Permoglaze Wood Preservative Clear. • On the treated timber, apply 1 coat of Permoglaze Aqua Lasure diluted with 5-10% water as sealing coat. • Allow to dry, then scuff with sandpaper. • Finally, apply 2 to 3 coats of slightly diluted Permoglaze Aqua Lasure. The freshly coated substrate should not be exposed to rain for a minimum of 48 hours. 	
APPLICATION	Method	Short Pile Roller & Brush
	Thinning	Clean, fresh water
	Dilution	First Coat Brush & Roller 5%
		Second Coat Brush & Roller Not Required
	Cleaning	Clean all equipment with water immediately after use
PRODUCT INFORMATION	Finish	Gloss
	Shades	Miel Dore, Ocre Terrerouge, Ambre Cannelle, Jaune de Chamarel, Caramel Roux, Brun-melasse (Other colours are available on request)
	Spreading Rate	10-12 m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	Drying Time	Touch Dry ±30 minutes at 25°C Recoating Time ± 3 hours at 25°C between coats
PRECAUTIONS	<ul style="list-style-type: none"> • Do not apply on wet, damp or rotten timber. • Varnish the end grain of the timber to prevent ingress of moisture. • Depending on exposure and use, a maintenance coat will be required within 1-3 years. Lightly sand the varnish before the new coats. • Never apply filler before using Permoglaze Aqua Lasure. • When applied on decking, heavy traffic will mechanically abrade and damage the varnish. 	

TECHNICAL DATA SHEETS

PERMOGLAZE AQUA LASURE

PACKAGING	Available in 1 & 5 litres
STORAGE	Store in a cool, dry and well-ventilated place.
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none">• Handle with care• Ensure good ventilation during application.• Avoid contact with skin and eyes.• If contact with skin occurs, wash well with soap and water• In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.• Keep out of reach of children.• Do not use empty paint containers for storing foodstuffs.• Do not throw paint containers or contents in the waterways or environment.• Contains no added Lead/Mercury/Nickel/Cadmium.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.