

TECHNICAL DATA SHEETS

PERMOGLAZE EGGSHELL

DESCRIPTION	Permoglaze Eggshell Finish is a high quality, structured finish for the decoration and protection of all interior surfaces. It can be applied on properly primed building materials such as timber and metal.									
CHARACTERISTICS	<ul style="list-style-type: none"> • Tough, hardwearing film when fully dried • Good opacity • Washable • Good sag resistance • Easy to apply • Resistant to mild acids • Good flow properties • Good water resistance • Good spreading rate 									
COMPOSITION	Based on a high-quality alkyd medium, blended with rutile titanium and other high-grade coloured pigments.									
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be free of dirt, dust, grease, oil and loose paint. • Mild Steel Surfaces: Rusts present on the surfaces should be scrapped off, followed by application of anticorrosion primer; Permoglaze Red Oxide Metal Primer and coated with Permoglaze Undercoat. Then, overcoat with Permoglaze Eggshell Finish. • Galvanised Steel Surfaces should be properly primed with 1 coat of Permoglaze Two Pack Etch Primer for better adhesion of subsequent coats and undercoated with 1 coat of Permoglaze Undercoat. Then, overcoat with Permoglaze Eggshell Finish. • Wood substrates should be primed with 1 coat of Permoglaze Wood Primer, then overcoat with Permoglaze Eggshell Finish. • 2-3 coats of Permoglaze Eggshell Finish are recommended for best performance. 									
APPLICATION	Method	Brush, Roller, Air-Assisted & Airless Spray								
	Thinning	Permoglaze Test Benzine								
	Dilution	<table border="0"> <tr> <td>Brush</td> <td>10-15%</td> </tr> <tr> <td>Roller</td> <td>5-10%</td> </tr> <tr> <td>Air-Assisted</td> <td>20-25%</td> </tr> <tr> <td>Airless Spray</td> <td>10-15%</td> </tr> </table>	Brush	10-15%	Roller	5-10%	Air-Assisted	20-25%	Airless Spray	10-15%
Brush	10-15%									
Roller	5-10%									
Air-Assisted	20-25%									
Airless Spray	10-15%									
	Cleaning	Permoglaze Test Benzine								

TECHNICAL DATA SHEETS

PERMOGLAZE EGGSHELL

PRODUCT INFORMATION	<p>Finish: Dries to a Smooth, Satin Lustre Finish</p> <p>Shades: White, pastel, medium & dark</p> <p>Spreading Rate: 8-10m²/liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode</p> <p>Drying Time: Touch Dry ±4 hours at 25°C between coats Recoating Time 12-16 hours at 25°C between coats</p>
PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. • Yellowing of the coating may occur due to the chemical nature of the product. • Yellowing is accelerated in darkness.
PACKAGING	Available in 1, 5 & 20 litres
STORAGE	Store in a cool, dry and well-ventilated place.
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> • Handle with care • Ensure good ventilation during application. • In case of insufficient ventilation during painting, wear suitable respiratory equipment. • Avoid contact with skin and eyes. • If contact with skin occurs, wash well with soap and water • In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. • Keep out of reach of children. • Do not use empty paint containers for storing foodstuffs. • Do not throw paint containers or contents in the waterways or environment. • Contains no added Lead/Mercury/Nickel/Cadmium.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.