

TECHNICAL DATA SHEETS

PERMOGLAZE LASURE

DESCRIPTION	Permoglaze Lasure is a one-component solvent-based modified alkyd varnish for all types of wood surfaces.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Suitable for both interior and exterior uses. • Durable and preserves the natural colour, beauty and grain of the timber. • Easy to apply by brush or air spray. • Good spreading rate. • Apply directly on bare, dry, clean and sound wood. • Provides different shades to suit different types of woods. 	
COMPOSITION	Modified alkyd resin	
SURFACE PREPARATION	<ul style="list-style-type: none"> • The surface must be clean and dry. • The timber must be treated with Permoglaze Wood Preservative Clear. • On the treated timber, apply 1 coat of Permoglaze Lasure diluted with 25-30% Permoglaze Test Benzine. • Allow to dry, then scuff with sandpaper. • Finally, apply 2 to 3 coats of slightly diluted Permoglaze Lasure. 	
APPLICATION	Method	Brush & Air Spray
	Thinning	Permoglaze Test Benzine
	Dilution	First Coat
		Brush 25-30%
		Air Spray 25-30%
		Second & Third Coat
		Brush 5-10%
		Air Spray 20-25%
	Cleaning	Clean all equipment with Permoglaze Test Benzine immediately after use.
PRODUCT INFORMATION	Finish	Gloss & satin
	Shades	Miel Dore, Ocre Terrerouge, Ambre Cannelle, Jaune de Chamarel, Caramel Roux, Brun-melasse (Other colours are available on request)
	Spreading Rate	10-12 m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	Drying Time	Touch Dry ± 2 hours at 25°C between coats
		Recoating Time ± 4 hours at 25°C between coats
PRECAUTIONS	<ul style="list-style-type: none"> • Do not apply on wet, damp or rotten timber. • Varnish the end grain of the timber to prevent ingress of moisture. • Depending on exposure and use, a maintenance coat will be required within 1-3 years. Lightly sand the varnish before the new coats. • When applied on decking, heavy traffic will mechanically abrade and damage the varnish. 	
PACKAGING	Available in 1,5 & 20 litres	
STORAGE	Store in a cool, dry and well-ventilated place.	

TECHNICAL DATA SHEETS

PERMOGLAZE LASURE

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Highly inflammable.
- Keep away from heat, sparks and open flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added **Lead/Mercury/Nickel/Cadmium**.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.