

TECHNICAL DATA SHEETS

PERMOGLAZE MATT FINISH

DESCRIPTION	<p>Permoglaze Matt Finish is a high-quality surface coating based on a modified alkyd medium with lightfast pigments to give outstanding performance. The system provides a washable, decorative and protective finish for interior surfaces. Permoglaze Matt Finish can be used on most primed building materials, including timber and metal.</p>									
CHARACTERISTICS	<ul style="list-style-type: none"> • Tough, flexible, washable film • Easy to apply • Very high durability • Excellent flow properties • Matt finish • High spreading rate 									
COMPOSITION	<p>A high-quality alkyd resin blended with rutile titanium and coloured pigments. No lead added.</p>									
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be free of dirt, dust, grease, oil and loose paint. • Mild Steel Surfaces: Rusted surfaces should be scrapped off, followed by application of anticorrosion primer, Permoglaze Red Oxide Metal Primer and Permoglaze Undercoat. Then, overcoat with Permoglaze Matt Finish. • Galvanised Steel Surfaces should be properly primed with 1 coat of Permoglaze Two Pack Etch Primer for better adhesion of subsequent coats and undercoated with 1 coat of Permoglaze Undercoat. Then, overcoat with Permoglaze Matt Finish. • Wood substrates should be primed with 1 coat of Permoglaze Wood Primer, then overcoat with Permoglaze Matt Finish. • 2-3 coats of Permoglaze Matt Finish are recommended for best performance. 									
APPLICATION	Method	Brush, Roller, Air-Assisted & Airless Spray								
	Thinning	Permoglaze Test Benzine								
	Dilution	<table border="0"> <tr> <td>Brush</td> <td>10-15%</td> </tr> <tr> <td>Short-pile Roller</td> <td>5-10%</td> </tr> <tr> <td>Air-Assisted</td> <td>20-25%</td> </tr> <tr> <td>Airless Spray</td> <td>10-15%</td> </tr> </table>	Brush	10-15%	Short-pile Roller	5-10%	Air-Assisted	20-25%	Airless Spray	10-15%
Brush	10-15%									
Short-pile Roller	5-10%									
Air-Assisted	20-25%									
Airless Spray	10-15%									
	Cleaning	Permoglaze Test Benzine								
PRODUCT INFORMATION	Finish	Matt								
	Shades	White, pastel, medium & dark								
	Spreading Rate	8-10m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode								
	Drying Time	<table border="0"> <tr> <td>Touch Dry</td> <td>±2 hours at 25°C between coats</td> </tr> <tr> <td>Recoating Time</td> <td>12-16 hours at 25°C between coats</td> </tr> </table>	Touch Dry	±2 hours at 25°C between coats	Recoating Time	12-16 hours at 25°C between coats				
Touch Dry	±2 hours at 25°C between coats									
Recoating Time	12-16 hours at 25°C between coats									

TECHNICAL DATA SHEETS

PERMOGLAZE MATT FINISH

PRECAUTIONS	<ul style="list-style-type: none">• The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.• Yellowing of the coating may occur due to the chemical nature of the product.• Yellowing is accelerated in darkness.
PACKAGING	Available in 250ml, 500 ml, 1, 5 & 20 litres
STORAGE	Store in a cool, dry and well-ventilated place.

SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none">• Handle with care• Ensure good ventilation during application.• In case of insufficient ventilation during painting, wear suitable respiratory equipment.• Avoid contact with skin and eyes.• If contact with skin occurs, wash well with soap and water• In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.• Keep out of reach of children.• Do not use empty paint containers for storing foodstuffs.• Do not throw paint containers or contents in the waterways or environment.• Contains no added Lead/Mercury/Nickel/Cadmium.
---	--

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.