

TECHNICAL DATA SHEETS

PERMOTOP

DESCRIPTION	Permotop Acrylic Emulsion MS3 is a high quality, water-based paint suitable for walls and ceilings on interior and exterior surfaces. Compliant with the Mauritius Standards Bureau MS3 standard, which specifies the requirements for emulsion paints for interior and exterior use.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Excellent obliterating power • Smooth, matt finish, hides surface imperfections • Economical • Washable • Fast and easy to apply • Alkali resistant • High spreading rate • Good flow properties • Structured to allow thinning • No residual odour • Quick drying 	
COMPOSITION	An emulsion-based paint formulated with a high durability acrylic resin and incorporating the highest quality pigments specially selected for their performance.	
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be free of dirt, dust, grease, oil and loose paint. • Surfaces infected by mould or algae growth must be treated with Permoglaze Biocidal Wall Wash, followed by Permoglaze Fungicidal Treatment. • Depending on the surface porosity, apply 1 coat of suitable primers such as; Permoglaze Clear Emulsion Binder, Permoglaze Aquaprime or Permoglaze Plaster Primer. • Leave to dry before applying Permotop Acrylic Emulsion MS3. • 3 coats are recommended for optimum performance of the paint. 	
APPLICATION	Method	Brush, Roller, Airless Spray
	Thinning	Water
	Dilution	1 st Coat Dilution volume ratio of 5 parts of paint to 1 part of water.
		2 nd & Dilution volume ratio of 10 parts of paint to 1 part of water.
		3 rd Coat
	Cleaning	Water

TECHNICAL DATA SHEETS

PERMOTOP

PRODUCT INFORMATION	<p>Finish: Decorative matt finish with a slight surface sheen when dry</p> <p>Shades: White, pastel, medium & dark</p> <p>Volume Solids: 35% - 45%</p> <p>Spreading Rate: ±10m²/liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode</p> <p>DFT: Dry film thickness will vary between 45 to 55 µm per coat on non-absorbent and smooth substrate.</p> <p>VOC: EU Limit for this product (cat A/c): 40g/l (2010). This product contains maximum 3.0g/L VOC.</p> <p>Drying Time: Touch Dry 30 minutes at 25°C Recoating Time 1-3 hours at 25°C between coats</p>
PRECAUTIONS	<ul style="list-style-type: none"> The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. Do not apply to very cold and damp surfaces.
PACKAGING	Available in 1, 5, 20 & 200 litres
STORAGE	Store in a cool, dry and well-ventilated place.
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> Handle with care Ensure good ventilation during application. In case of insufficient ventilation during painting, wear suitable respiratory equipment. Avoid contact with skin and eyes. If contact with skin occurs, wash well with soap and water In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. Keep out of reach of children. Do not use empty paint containers for storing foodstuffs. Do not throw paint containers or contents in the waterways or environment. Contains no added Lead/Mercury/Nickel/Cadmium.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.