

TECHNICAL DATA SHEETS

PERMOGLAZE TIMBERCOAT EXTERIOR VARNISH

DESCRIPTION	Permoglaze Timbercoat Exterior Varnish is a highly durable synthetic resin-based varnish containing an ingredient that absorbs ultra-violet while extending the life span of the film and preserving the natural colour and grain of the timber. It is particularly recommended for exterior application.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Clear, sharp and attractive • Outstanding durability • Fast and easy to apply • Good spreading rate • Contains material for protection and longevity of the wood 	
COMPOSITION	Alkyd resin based medium with special penetrating solvents.	
SURFACE PREPARATION	All surfaces must be properly prepared to provide thoroughly dry and clean timber, free from grease, wax and dirt prior to coating.	
	NEW WOODWORK	
	<ul style="list-style-type: none"> • New exterior woodwork must be clean, dry and well sanded. • Thin first coat with 10% Permoglaze Test Benzine Second and third coats should be applied unthinned. • Sand lightly between coats. 	
	PREVIOUSLY VARNISHED SURFACES	
	<ul style="list-style-type: none"> • Sound surfaces should be well sanded. Surfaces which are cracked, and flaking must be stripped to bare wood by sanding with abrasive paper. • Interior woodwork should be wiped down with Permoglaze Test Benzine to remove wax and oil. • Follow with a water rinse. • For maximum protection of exterior timber, apply three coats of varnish. 	
APPLICATION	Method	Brush or air-assisted spray
	Thinning	Permoglaze Test Benzine
	Cleaning	Permoglaze Test Benzine
PRODUCT INFORMATION	Finish	Gloss & Satin
	Shades	Tinted & clear
	Spreading Rate	10-12m ² /litre depending on surface, ambient conditions, colour, dilution and application method
	Drying Time	Touch Dry 4-6 hours depending on atmospheric conditions
PRECAUTIONS	<ul style="list-style-type: none"> • It is important to varnish the end grain of exterior timber to prevent ingress of moisture. • Do not apply to wet or damp timber. • Pretreat all exterior woodwork with Permoglaze Wood Preservative prior to applying varnish. 	
PACKAGING	Available in 1, 5 & 20 litres	
STORAGE	Keep in a cool, dry place and away from heat sources.	

TECHNICAL DATA SHEETS

PERMOGLAZE TIMBERCOAT EXTERIOR VARNISH

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Flammable. Keep away from sparks, heat and naked flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added Lead/Mercury/Nickel/Cadmium.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.