

TECHNICAL DATA SHEETS

PERMOGLAZE UNIVERSAL WOOD VARNISH

DESCRIPTION	Permoglaze Universal Wood Varnish is a protective decorative varnish for use on most species of hard and soft woods. Designed for interior uses, it enhances the natural appearance of the wood grain.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Economical product • Fast and easy to apply • Good spreading rate • Recommended for interior use • Contains no UV light absorbers – less resistant to the development of heat energy and infra-red from the sun • Gives a good full gloss with a high degree of acceptance 	
COMPOSITION	Alkyd resin-based medium with special penetrating solvents	
SURFACE PREPARATION	<ul style="list-style-type: none"> • The surface must be clean and dry. • The timber must be treated with Permoglaze Wood Preservative Clear. • Colour of the timber can be changed by using woodstain and overcoat with Permoglaze Universal Wood Varnish. • For satin and matt, the Permoglaze Universal Wood Varnish must be well stirred before use, so as to obtain a uniform finish. 	
APPLICATION	Method	Brush, Short pile Roller, & Air Spray
	Thinning	Permoglaze Test Benzine
	Dilution	Brush 10-15%
		Roller 5-10%
		Air-Spray 20-25%
	Cleaning	Clean all equipment with Permoglaze Test Benzine immediately after use.
PRODUCT INFORMATION	Finish	Gloss, Satin & Matt
	Shades	Clear, gloss tinted, satin & matt tinted
	Spreading Rate	8-10 m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	Drying Time	Touch Dry ± 6 hours at 25°C
		Recoating Time ± 12 hours at 25°C between coats (without sanding)
PRECAUTIONS	<ul style="list-style-type: none"> • Do not apply on wet, damp or rotten timber. • Varnish the end grain of the timber to prevent ingress of moisture. 	
PACKAGING	Available in 500ml, 1, 5 & 20 litres	
STORAGE	Store in a cool, dry and well-ventilated place.	

TECHNICAL DATA SHEETS

PERMOGLAZE UNIVERSAL WOOD VARNISH

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Highly inflammable.
- Keep away from heat, sparks and open flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added **Lead/Mercury/Nickel/Cadmium**.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.