

## TECHNICAL DATA SHEETS

### PERMOGLAZE VIP SATIN

<b>DESCRIPTION</b>	Permoglaze VIP Satin is a high-quality water-based paint. It dries to give an even, attractive silk finish. It is used for decoration and protection of interior surfaces.		
<b>CHARACTERISTICS</b>	<ul style="list-style-type: none"> <li>• Easy to apply with high spreading rate</li> <li>• Excellent colour retention</li> <li>• Good flow properties</li> <li>• No residual odour</li> <li>• Flexible and washable</li> </ul>		
<b>COMPOSITION</b>	Emulsion paint based on a high durability polymeric medium and incorporating pigments with lightfast qualities.		
<b>SURFACE PREPARATION</b>	<ul style="list-style-type: none"> <li>• Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.</li> <li>• Surfaces must be free of dirt, dust, grease, oil and loose paint.</li> <li>• Surfaces infected by mould or algae growth must be treated with <b>Permoglaze Biocidal Wall Wash</b>, followed by <b>Permoglaze Fungicidal Treatment</b>.</li> <li>• Bare and porous concrete surfaces must be washed thoroughly with water then primed with 1 coat of <b>Permoglaze Aqua Prime</b> for maximum opacity.</li> <li>• Leave to dry before applying <b>Permoglaze VIP Satin</b>.</li> <li>• 3 coats are recommended for optimum performance of the paint.</li> </ul>		
<b>APPLICATION</b>	Method	Brush, Roller, Airless Spray	
	Thinning	Water	
	Dilution	1 <sup>st</sup> Coat	Dilution volume ratio of 5 parts of paint to 1 part of water.
		2 <sup>nd</sup> & 3 <sup>rd</sup> Coat	Dilution volume ratio of 10 parts of paint to 1 part of water.
	Cleaning	Water	
<b>PRODUCT INFORMATION</b>	Finish	Attractive, Silk Sheen Finish	
	Shades	White, pastel, medium & dark	
	Volume Solids	35-40 %	
	Spreading Rate	8-10 m <sup>2</sup> /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode	
	DFT	Dry film thickness will vary between 40 to 50 µm per coat on non-absorbent and smooth substrate.	
	VOC	EU Limit for this product (cat A/b) : 100g/l (2010). This product contains maximum 3g/l VOC.	
	Drying Time	Touch Dry	45 minutes at 25°C
		Recoating Time	1-3 hours at 25°C between coats

## TECHNICAL DATA SHEETS

### PERMOGLAZE VIP SATIN

<b>PRECAUTIONS</b>	<ul style="list-style-type: none"><li>• The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.</li><li>• Recommended for interior use.</li><li>• It is preferable to use undiluted so as to obtain an even finish.</li><li>• Not recommended for ceilings as it may show the imperfections of the surface.</li></ul>
<b>PACKAGING</b>	Available in 1, 5, 20 & 200 litres
<b>STORAGE</b>	Store in a cool, dry and well-ventilated place.
<b>SAFETY, HEALTH &amp; ENVIRONMENT INFORMATION</b>	<ul style="list-style-type: none"><li>• Handle with care</li><li>• Ensure good ventilation during application.</li><li>• In case of insufficient ventilation during painting, wear suitable respiratory equipment.</li><li>• Avoid contact with skin and eyes.</li><li>• If contact with skin occurs, wash well with soap and water</li><li>• In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.</li><li>• Keep out of reach of children.</li><li>• Do not use empty paint containers for storing foodstuffs.</li><li>• Do not throw paint containers or contents in the waterways or environment.</li><li>• Contains no added <b>Lead/Mercury/Nickel/Cadmium</b>.</li></ul>

For further information, kindly contact our Technical Information Service.

**Note:** This Technical Data Sheet is subject to change without prior notice.

#### DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.