

TECHNICAL DATA SHEETS

PERMOGLAZE 2 K ACRYLIC THINNER

DESCRIPTION	Permoglaze 2K Acrylic Thinner is a diluent for Permoglaze 2K Acrylic based paints, primers and varnishes.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Medium evaporating solvent • Can also be used to dilute Permoglaze Two Pack Polyurethane 	
COMPOSITION	A blend of aromatic solvents, ketone and acetate	
PRODUCT INFORMATION	Specific Gravity	0.85 – 0.86
	Shades	Clear Liquid
PACKAGING	Available in 1, 5 & 20 litres	
STORAGE	Keep away from direct sun, sources of heat, flames or sparks.	
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> • Highly inflammable. • Keep away from heat, sparks and open flames. • Handle with care • Ensure good ventilation during application. • In case of insufficient ventilation during painting, wear suitable respiratory equipment. • Avoid contact with skin and eyes. • If contact with skin occurs, wash well with soap and water • In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. • Keep out of reach of children. • Do not use empty paint containers for storing foodstuffs. • Do not throw paint containers or contents in the waterways or environment. • Contains no added Lead/Mercury/Nickel/Cadmium. 	

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.