

## TECHNICAL DATA SHEETS

### PERMOGLAZE BITUKOTE

<b>DESCRIPTION</b>	PermoGlaze Bitukote is a cut-back bituminous brickwork waterproof coating to be applied on plaster and concrete. Can also be applied as a waterproof layer and damp proofing sealer.	
<b>SURFACE PREPARATION</b>	<ul style="list-style-type: none"> <li>Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.</li> <li>Surfaces must be free of dirt, dust, loose rust, grease, oil and loose paint.</li> </ul>	
<b>APPLICATION</b>	Method	It is recommended to apply two coats by means of block brush to ensure that any pinholes after the first coat are completely obliterated.
	Thinning	PermoGlaze Test Benzine
	Cleaning	Wash equipment with PermoGlaze Test Benzine immediately after use.
<b>PRODUCT INFORMATION</b>	Finish	Gloss
	Shades	Black
	Volume Solids	
	Recommended DFT	µm per coat
	Recommended WFT	µm per coat
	Theoretical Spreading Rate	11.7 m <sup>2</sup> /L @ 30 µm on a smooth surface. This serves as a guide only
	Practical Spreading Rate	The practical spreading rate will vary depending on the profile of the substrate, as well as the application technique and tools used
	Spreading Rate/Litre	± 4m <sup>2</sup> depending on surface profile, ambient conditions, dilution and application method
	Drying Time	8-24 hours
Components	One-pack	
Shelf Life	18-24 months	
<b>PRECAUTIONS</b>	The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.	
<b>PACKAGING</b>	Available in 5 & 20 litres	
<b>STORAGE</b>	Keep in a cool, dry place and away from heat sources.	

## TECHNICAL DATA SHEETS

### PERMOGLAZE BITUKOTE

#### SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Highly inflammable.
- Keep away from heat, sparks and open flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added **Lead/Mercury/Nickel/Cadmium**.

For further information, kindly contact our Technical Information Service.

**Note:** This Technical Data Sheet is subject to change without prior notice.

#### DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.