

TECHNICAL DATA SHEETS

PERMOGLAZE BITULAC

DESCRIPTION	Permoglaze Bitulac is an alkyd-based general-purpose finishing coat for alkyd-based paint systems on wood and metallic surfaces.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Tough, flexible, washable film • Easy to apply • Good durability • Excellent flow properties • Good colour retention • Good spreading rate 	
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Ensure that all surfaces are clean, sound and grease-free. • Previously painted surfaces should be rubbed down with glass paper and new surfaces should be primed. 	
APPLICATION	Method	Brush, Short pile roller, Conventional air-assisted spray or Airless spray.
	Thinning	Permoglaze Test Benzine
	Cleaning	Wash equipment with Permoglaze Test Benzine immediately after use.
PRODUCT INFORMATION	Finish	Gloss
	Shades	Grey, black, red & green
	Spreading Rate	± 10m ² /litre depending on surface profile, ambient conditions, dilution and application method
	Drying Time	Surface Dry 3-4 hours Hard Dry 12-16 hours
PRECAUTIONS	The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.	
PACKAGING	Available in 5 & 20 litres	
STORAGE	Keep in a cool, dry place and away from heat sources.	
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> • Handle with care • Ensure good ventilation during application. • In case of insufficient ventilation during painting, wear suitable respiratory equipment. • Avoid contact with skin and eyes. • If contact with skin occurs, wash well with soap and water • In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. • Keep out of reach of children. • Do not use empty paint containers for storing foodstuffs. • Do not throw paint containers or contents in the waterways or environment. • Contains no added Lead/Mercury/Nickel/Cadmium. 	

TECHNICAL DATA SHEETS

PERMOGLAZE BITULAC

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.

TECHNICAL DATA SHEETS

PERMOGLAZE BITULAC