

TECHNICAL DATA SHEETS

PERMOGLAZE CHLORINATED ROAD MARKING MS 87

DESCRIPTION	Permoglaze Road Marking MS 87 is specially manufactured on a chlorinated rubber/alkyd blend for the marking lines on road surfaces or where an exceptionally water repellent coating is required	
CHARACTERISTICS	<ul style="list-style-type: none"> • Excellent film build • Quick drying road line paint with excellent road service • Very good overcoating properties • Direct application to all types of new or previously painted bituminous and concrete road surfaces • Excellent day and night visibility • Good flow and low creep make it an ideal product for sign writing on roads and exterior parking lots 	
COMPOSITION	Chlorinated polymers/alkyd	
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Bituminous and concrete surfaces must be clean, dry and free from loose gravel. 	
APPLICATION	Method	<ul style="list-style-type: none"> • Brush or roller. For spray application, thin with Permoglaze Slow Aromatic Solvent. • Apply one round coat in accordance with the spreading rate given. <p>Note: As this material is quick drying, do not attempt to work the brush or roller too much over the same area. It should be applied by "laying on" an even coat.</p>
	Thinning	Permoglaze Slow Aromatic Solvent.
	Cleaning	Permoglaze Slow Aromatic Solvent.
PRODUCT INFORMATION	Finish	Matt
	Shades	White, black, yellow & red
	Spreading Rate	± 10m ² /litre depending on surface, ambient conditions, colour, dilution and application method
	Drying Time	Touch Dry ± 20 minutes depending on dilution, wet film thickness, substrates, ambient conditions and application method
		Recoating Time Minimum: ±1 hour Maximum: Indefinite
	Pigmentation Component	Inert pigments Single pack
PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. • Not recommended for car showroom floors since it soils easily due to its matt appearance. • Not recommended as a cure for damp problems. 	
PACKAGING	Available in 1, 5 & 20 litres	
STORAGE	Keep in a cool, dry place and away from heat sources.	

TECHNICAL DATA SHEETS

PERMOGLAZE CHLORINATED ROAD MARKING MS 87

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Highly inflammable.
- Keep away from heat, sparks and open flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added **Lead/Mercury/Nickel/Cadmium**.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.