

TECHNICAL DATA SHEETS

PERMOGLAZE CLEAR EMULSION BINDER

DESCRIPTION	<p>Permoglaze Clear Emulsion Binder is a water-based sealer for application on concrete surfaces. It is formulated on a durable medium for interior and exterior uses. It is highly effective for sealing porous and dusty surfaces and enhances the adhesion of new coatings on existing ones, which may have chalked because of external exposure.</p>	
CHARACTERISTICS	<ul style="list-style-type: none"> • High durability • Flexible Fast and easy to apply • Quick drying • Transparent • Good adhesion on all surfaces • Good spreading rate • Good flow properties 	
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be clean, sound and free from loose material. • On wallpaper, it is recommended to first test the product on a small area to ensure that there are no water-soluble dyes. 	
APPLICATION	Method	<p>Brush or conventional air-assisted spray.</p> <p><u>Note</u></p> <ul style="list-style-type: none"> • On wallpaper and bare interior woodwork, apply 2 coats unthinned. • On emulsion or flat oil paint as a sheen, apply 1 coat thinned with 1-part water to 4 parts Permoglaze Clear Emulsion Binder. • On smooth, dry shuttering timber, apply a first coat thinned with 1-part water to 4 parts Permoglaze Clear Emulsion Binder and a second coat unthinned.
	Thinning	Clean, fresh water
	Cleaning	Wash equipment with clean water immediately after use.
PRODUCT INFORMATION	Shades	Transparent
	Spreading Rate	± 12m ² /litre depending on surface, ambient conditions, colour, dilution and application method
	Drying Time	Touch Normally dry in ± 1 hour depending on atmospheric conditions Dry
PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. • Do not apply to very cold surfaces. 	
PACKAGING	Available in 1, 5, 20 & 200 litres	
STORAGE	Keep in a cool, dry and well-ventilated place.	

TECHNICAL DATA SHEETS

PERMOGLAZE CLEAR EMULSION BINDER

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added **Lead/Mercury/Nickel/Cadmium**.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.