

TECHNICAL DATA SHEETS

PERMOGLAZE ETCH SOLUTION

DESCRIPTION	Permoglaze Etch Solution is a concentrated blend of acids for etching of metals and masonry surfaces.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Excellent etching solution for non-ferrous surfaces such as galvanised steel, aluminium and concrete • Washes off easily with water • Provides an efficient key for future coating • Simple to use, excellent for rust removal 	
COMPOSITION	20% blend of monobasic acids	
APPLICATION	Method	Apply by brush, sponge or pad. Allow to react on surface for a few minutes, then rinse off thoroughly with water.
	Cleaning	Wash equipment with clean water immediately after use.
PRODUCT INFORMATION	Shades	Colorless
	PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. • Permoglaze Etch Solution is an acid solution and the use of this product should be restricted to qualified personnel.
PACKAGING	Available in 1 & 5 litres	
STORAGE	Keep in a cool, dry place and away from heat sources.	
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> • Handle with care • Ensure good ventilation during application. • In case of insufficient ventilation during painting, wear suitable respiratory equipment. • Avoid contact with skin and eyes. • If contact with skin occurs, wash well with soap and water • In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. • Keep out of reach of children. • Do not use empty paint containers for storing foodstuffs. • Do not throw paint containers or contents in the waterways or environment. • Contains no added Lead/Mercury/Nickel/Cadmium. 	

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.