

TECHNICAL DATA SHEETS

PERMOGLAZE GP ALUMINIUM

DESCRIPTION	Permoglaze GP Aluminium consists of aluminium flakes dispersed in a non- acid medium, suitable for interior and exterior application on suitably primed surfaces.							
CHARACTERISTICS	<ul style="list-style-type: none"> • General purpose high lustre aluminium • Excellent durability • Reflects heat 							
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces to be painted must be thoroughly dried before painting. Brush off all dirt, efflorescence and loose material. • Apply the primers; Permoglaze PA 10 Primer or Permoglaze Two Pack Etch Primer, followed by Permoglaze GP Aluminium. • 2-3 coats of Permoglaze GP Aluminium are recommended for optimum performance. 							
APPLICATION	Method	Brush, Short Pile Roller or Air-assisted spray						
	Thinning	Permoglaze Test Benzine						
	Dilution	<table border="0"> <tr> <td>Brush</td> <td>Ready for use</td> </tr> <tr> <td>Roller</td> <td>Ready for use</td> </tr> <tr> <td>Air-assisted spray</td> <td>5%</td> </tr> </table>	Brush	Ready for use	Roller	Ready for use	Air-assisted spray	5%
Brush	Ready for use							
Roller	Ready for use							
Air-assisted spray	5%							
	Cleaning	Wash equipment with Permoglaze Test Benzine immediately after use.						
PRODUCT INFORMATION	Finish	Matt						
	Shades	Gloss silver						
	Spreading Rate	10-15m ² /Litre depending on surface, ambient conditions, colour, dilution and application method						
	Drying Time	<table border="0"> <tr> <td>Touch Dry</td> <td>± 4 hours</td> </tr> <tr> <td>Hard Dry</td> <td>± 16 hours</td> </tr> </table>	Touch Dry	± 4 hours	Hard Dry	± 16 hours		
Touch Dry	± 4 hours							
Hard Dry	± 16 hours							
	Pigmentation Component	Aluminium flakes Single pack						
PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. 							
PACKAGING	Available in 250 ml, 500 ml, 1, 5 & 20 litres.							
STORAGE	Store in a cool, dry place and away from heat sources.							

TECHNICAL DATA SHEETS

PERMOGLAZE GP ALUMINIUM

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Highly inflammable.
 - Keep away from heat, sparks and open flames.
 - Handle with care
 - Ensure good ventilation during application.
 - In case of insufficient ventilation during painting, wear suitable respiratory equipment.
 - Avoid contact with skin and eyes.
 - If contact with skin occurs, wash well with soap and water
 - In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
 - Keep out of reach of children.
 - Do not use empty paint containers for storing foodstuffs.
 - Do not throw paint containers or contents in the waterways or environment.
 - Contains no added **Lead/Mercury/Nickel/Cadmium**.
-

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.