

TECHNICAL DATA SHEETS

PERMOGLAZE PA 10 PRIMER

DESCRIPTION	Permolaze PA 10 Primer is a specially formulated primer combining etching and pre-treatment qualities in one application for the preparation of ferrous and non-ferrous surfaces.	
PURPOSE	Offers superior adhesion and is particularly suitable as a blast primer. Properties include active chemicals which assist in combating atmospheric pollution deposits.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Economical • Good corrosion resistance • Excellent adhesion • Fast and easy to apply • Interior and exterior use • High spreading rate • Provides a good foundation for subsequent coats of paint 	
COMPOSITION	Based on a natural red oxide pigment dispersed in a specially formulated synthetic resin medium. No lead added.	
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be free of dirt, dust, grease, oil and loose paint. • The performance of this primer will depend upon the degree of surface preparation, therefore blast cleaning to Swedish Standard SA 2.5 is recommended. 	
APPLICATION	Method	Brush, Short Pile Roller & Spray
	Thinning	Permolaze PA 10 Thinner
	Cleaning	Permolaze PA 10 Thinner
PRODUCT INFORMATION	Finish	Matt
	Shades	Red Oxide
	Spreading Rate	8-10m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	Drying Time	Touch Dry 10-15 mins at 25°C between coats
	Recoating Time	Maximum 12 hours at 25°C between coats
PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. 	
PACKAGING	Available in 500ml, 1, 5 & 20 litres.	
STORAGE	Store in a cool, dry and well-ventilated place.	

TECHNICAL DATA SHEETS

PERMOGLAZE PA 10 PRIMER

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Highly inflammable.
- Keep away from heat, sparks and open flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Do not use empty paint containers for storing foodstuffs.
 - Do not throw paint containers or contents in the waterways or environment.
 - Contains no added **Lead/Mercury/Nickel/Cadmium**.
-

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.