

TECHNICAL DATA SHEETS

PERMOGLAZE PERMOFILL

DESCRIPTION	Permofill is a ready-mixed, white and slightly granular paste based on fillers and water-reducible resins. It dries after application to a tough, rigid weather-resistant filling. Permofill is designed for filling cracks and holes in and around interior and exterior plaster, brick, stone, concrete and other masonry surfaces.		
CHARACTERISTICS	<ul style="list-style-type: none"> • Thixotropic • Smooth paste • Minimal shrinkage • Fast and easy to apply • Excellent adhesion • Water resistant when dry 		
COMPOSITION	Water reducible thixotropic paste		
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be firm, free of dust and loose material 		
APPLICATION	Method	<ul style="list-style-type: none"> • Apply Permofill with a putty knife. • Permofill is difficult to sand and is best smoothed while wet. • Protect from moisture during the drying period. • Pre-wet surfaces to be filled where possible. 	
	Cleaning	Wash equipment with clean, fresh water immediately after use.	
PRODUCT INFORMATION	Shades	White	
	Spreading Rate	Depending on the size of cracks	
	Drying Time	Touch Dry ± 1 hour at 25°C depending on thickness	
PRECAUTIONS	<ul style="list-style-type: none"> • The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. 		
PACKAGING	Available in 1, 5 & 20 litres		
STORAGE	Store in a cool, dry and well-ventilated place.		
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> • Handle with care • Ensure good ventilation during application. • In case of insufficient ventilation during painting, wear suitable respiratory equipment. • Avoid contact with skin and eyes. • If contact with skin occurs, wash well with soap and water • In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. • Keep out of reach of children. • Do not use empty paint containers for storing foodstuffs. • Do not throw paint containers or contents in the waterways or environment. • Contains no added Lead/Mercury/Nickel/Cadmium. 		

TECHNICAL DATA SHEETS

PERMOGLAZE PERMOFILL

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.