

TECHNICAL DATA SHEETS

PERMOGLAZE QUICK DRY ENAMEL

DESCRIPTION	Permoglaze Quick Dry Enamel is a high-quality surface coating manufactured on an alkyd medium with lightfast pigments to give outstanding performance. It provides a tough flexible film. It may be washed repeatedly, has very low dirt retention and is quick drying. It is a good industrial finish for the protection of metal and wood surfaces. Recommended for interior and exterior use.	
CHARACTERISTICS	<ul style="list-style-type: none"> • Tough, flexible, washable film • Excellent flow properties • Very high durability and good colour retention • Resistant to mild acids and normal atmospheric pollution • Quick drying • Easy to apply 	
COMPOSITION	High quality modified alkyd resin blended with rutile titanium and coloured pigments.	
SURFACE PREPARATION & APPLICATION	<ul style="list-style-type: none"> • The preparation of the surface before application needs proper care and attention to add life and appearance to the final finish. • Where the condition of the existing surface is suspect, it should be stripped to bare metal. • All surfaces must be clean, dry and free from flaking paint, rust or oil. • As a precaution, wipe surfaces with Permoglaze Lacquer Thinner and allow to dry. 	
	Thinning	Permoglaze Test Benzine
	Cleaning	Permoglaze Test Benzine
PRODUCT INFORMATION	Finish	Gloss
	Shades	White, pastel, medium & dark
	Spreading Rate	8-10 m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	Drying Time	Touch dry ± 1 hour
		Hard Dry ± 2 hours
PRECAUTIONS	<ul style="list-style-type: none"> • Yellowing of the coating may occur due to the chemical nature of the product. • Yellowing is accelerated in darkness. 	
PACKAGING	Available in 1 & 20 litres	
STORAGE	Keep in a cool, dry place and away from heat sources.	

TECHNICAL DATA SHEETS

PERMOGLAZE QUICK DRY ENAMEL

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Flammable. Keep away from sparks, heat and naked flames.
- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added **Lead/Mercury/Nickel/Cadmium**.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.