

## TECHNICAL DATA SHEETS

### PERMOGLAZE SKIMFILL

<b>DESCRIPTION</b>	Permoglaze Skimfill is an acrylic paste used for rendering of cement plaster, skimming over defects in plaster work, skimming after alterations or renovations to join new and old surfaces.	
<b>CHARACTERISTICS</b>	<ul style="list-style-type: none"> <li>• Can be overcoated with water-based paint coatings</li> <li>• Can be used as crack filler</li> <li>• Ready-mixed</li> </ul>	
<b>SURFACE PREPARATION</b>	<ul style="list-style-type: none"> <li>• Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.</li> <li>• All surfaces must be properly prepared to be clean, free of dust, grease, wax, loose paint and dirt prior to application.</li> <li>• Surfaces with fungal growth must be treated with <b>Permoglaze Biocidal Wall Wash</b> and <b>Permoglaze Fungicidal Treatment</b> before applying <b>Permoglaze Skimfill</b>.</li> </ul>	
<b>APPLICATION</b>	Method	<ul style="list-style-type: none"> <li>• Apply with either a steel trowel or scraper.</li> <li>• Apply to a very smooth finish.</li> <li>• <b>Permoglaze Skimfill</b> can be sanded when dry (4 hours) depending on thickness. 100 grit or finer sandpaper is recommended.</li> </ul>
	Thinning	Not recommended
	Cleaning	Wash equipment with clean water immediately after use.
<b>PRODUCT INFORMATION</b>	Finish	Smooth matt
	Shades	White
	Spreading Rate	± 5m <sup>2</sup> /5 litres at 2mm thickness
	Binder Type	Acrylic-based
	Drying Time	Touch Dry ± 1½ hour at 25°C in dry conditions (depending on thickness) Hard Dry ± 4 hours at 25°C in dry conditions (depending on thickness) Recoating ± 4 hours minimum in dry conditions Times
<b>PRECAUTIONS</b>	<ul style="list-style-type: none"> <li>• The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.</li> <li>• Only one coat is recommended.</li> <li>• Do not apply on chalky and powdery surfaces.</li> <li>• Allow product to dry thoroughly before overcoating.</li> </ul>	
<b>PACKAGING</b>	Available 5 & 20 litres	
<b>STORAGE</b>	Store in a cool, dry and well-ventilated place.	

## TECHNICAL DATA SHEETS

### PERMOGLAZE SKIMFILL

---

#### SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Handle with care
  - Ensure good ventilation during application.
  - In case of insufficient ventilation during painting, wear suitable respiratory equipment.
  - Avoid contact with skin and eyes.
  - If contact with skin occurs, wash well with soap and water
  - In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
  - Keep out of reach of children.
  - Do not use empty paint containers for storing foodstuffs.
  - Do not throw paint containers or contents in the waterways or environment.
  - Contains no added **Lead/Mercury/Nickel/Cadmium**.
- 

For further information, kindly contact our Technical Information Service.

**Note:** This Technical Data Sheet is subject to change without prior notice.

#### DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.