

TECHNICAL DATA SHEETS

PERMOGLAZE TEST BENZINE

| | | |
|---|--|-------------------|
| DESCRIPTION | Permoglaze Test Benzine is a diluent for alkyd-based sealers, paints, primers and varnishes. | |
| CHARACTERISTICS | <ul style="list-style-type: none"> • Slow evaporating solvent • Economical | |
| COMPOSITION | An aromatic and aliphatic blend | |
| PRODUCT INFORMATION | Specific Gravity | 0.774 |
| | Shades | Colourless liquid |
| PACKAGING | Available in 1, 5, 20 & 200 litres | |
| STORAGE | Keep away from direct sun, sources of heat, flames or sparks. | |
| SAFETY, HEALTH & ENVIRONMENT INFORMATION | <ul style="list-style-type: none"> • Highly inflammable. • Keep away from heat, sparks and open flames. • Handle with care • Ensure good ventilation during application. • In case of insufficient ventilation during painting, wear suitable respiratory equipment. • Avoid contact with skin and eyes. • If contact with skin occurs, wash well with soap and water • In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. • Keep out of reach of children. • Do not use empty paint containers for storing foodstuffs. • Do not throw paint containers or contents in the waterways or environment. • Contains no added Lead/Mercury/Nickel/Cadmium. | |

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.