

## TECHNICAL DATA SHEETS

### PERMOGLAZE WOOD PRESERVATIVE

<b>DESCRIPTION</b>	<p><b>Permoglaze Wood Preservative</b> is a deep penetrating solution with bactericides for the protection of timber prior to the application of paint and varnishes. Ideal for all new exterior wooden surfaces such as windows, doors, fascia boards and barge boards, where a durable waterproof dressing is required. Since <b>Permoglaze Wood Preservative</b> is a penetrating type of dressing, previously varnished surfaces must be sanded back to bare wood to allow the material to soak well into the surface</p>	
<b>CHARACTERISTICS</b>	<ul style="list-style-type: none"> <li>• <b>Permoglaze Wood Preservative</b> is not a varnish – it will not flake, crack or disintegrate on timber</li> <li>• It is not difficult to apply – flows on with a brush with little or no effort. All the exterior woodwork can be treated in one day</li> <li>• Based on proven international formulating experience which gives a deep-down protection</li> <li>• Economical way of giving long-lasting protection</li> <li>• <b>Permoglaze Wood Preservative</b> is not a paint and will not hide the wood</li> <li>• Unlike conventional wood dressings, it is faster drying, greatly reducing coating period and dirt pick-up</li> <li>• Not difficult to maintain – once the first coat has worn through, simply apply another coat – saves time and money</li> </ul>	
<b>COMPOSITION</b>	Synthetic resin, solvent and bactericides.	
<b>SURFACE PREPARATION</b>	<ul style="list-style-type: none"> <li>• Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.</li> <li>• Surfaces must be free of dirt, dust, grease, oil and loose paint.</li> </ul> <p><b>NEW WOODWORK</b></p> <ul style="list-style-type: none"> <li>• New woodwork must be clean, dry and well sanded. For maximum protection, three full coats must be applied.</li> </ul> <p><b>PREVIOUSLY VARNISHED SURFACES</b></p> <ul style="list-style-type: none"> <li>• Not difficult to maintain – once the first coat has worn through, simply apply another coat – saves time and money</li> <li>• Sand and remove all the previous coatings. This will allow the <b>Permoglaze Wood Preservative</b> to penetrate the fibres and seal the surface.</li> <li>• Surfaces previously treated with <b>Permoglaze Wood Preservative</b> or similar should be wiped down with <b>Permoglaze Test Benzine</b> to remove dirt and grime.</li> <li>• Apply one to two coats as necessary.</li> </ul>	
<b>APPLICATION</b>	Method	Brush & Air-assisted spray
	Dilution	Brush Ready for use. Stir well before use and allow the material to soak well into new timber by applying liberally.
		Air-assisted spray Ready for use.
	Thinning	Not Recommended
	Cleaning	Permoglaze Test Benzine

## TECHNICAL DATA SHEETS

### PERMOGLAZE WOOD PRESERVATIVE

<b>PRODUCT INFORMATION</b>	Shades Spreading Rate/litre Drying Time	Clear ±10m <sup>2</sup> depending on surface, ambient conditions, colour, dilution and application methods Unlike conventional varnishes, <b>PermoGlaze Wood Preservative</b> requires several days to dry
<b>PRECAUTIONS</b>	<ul style="list-style-type: none"> <li>The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.</li> </ul>	
<b>PACKAGING</b>	Available in 1, 5 & 20 litres	
<b>STORAGE</b>	Keep in a cool, dry place and away from heat sources	
<b>SAFETY, HEALTH &amp; ENVIRONMENT INFORMATION</b>	<ul style="list-style-type: none"> <li>Handle with care</li> <li>Ensure good ventilation during application.</li> <li>In case of insufficient ventilation during painting, wear suitable respiratory equipment.</li> <li>Avoid contact with skin and eyes.</li> <li>If contact with skin occurs, wash well with soap and water</li> <li>In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.</li> <li>Keep out of reach of children.</li> <li>Do not use empty paint containers for storing foodstuffs.</li> <li>Do not throw paint containers or contents in the waterways or environment.</li> <li>Contains no added <b>Lead/Mercury/Nickel/Cadmium</b>.</li> </ul>	

For further information, kindly contact our Technical Information Service.

**Note:** This Technical Data Sheet is subject to change without prior notice.

#### DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.