


# ARUSHA

An eco-friendly, low VOC water-based, premium textured finish coating.



### Apply with

---

- Lamb's wool roller
- Block brush
- Stippled Roller



### Recommended for

---

Interior and exterior wall surfaces such as cement plaster, concrete, masonry, gypsum, plasterboard, wood and metal.

# TRIBE

## SURFACE PREPARATION

---

- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surfaces infected by mould or algae growth must be treated with the appropriate product.
- Bare new concrete surfaces must be cleaned with water and then primed with 1 diluted coat of water-based acrylic paint for maximum opacity.
- On skimmed and porous surfaces, 1 coat of appropriate primer must be applied.

## PRODUCT APPLICATION:

---

### APPLICATION OF THE PRIMER

- Using a roller, apply 1 even coat of **TRIBE Textured Acrylic Primer** tinted to the chosen shade of **TRIBE Arusha**. Allow 4-6 hours to dry.

### APPLICATION OF TRIBE ARUSHA

- Using a lamb's wool roller, apply a 1<sup>st</sup> coat of **TRIBE Arusha**.
- Then using a block brush, float to create the desired finish (vertical or swirl pattern).
- Allow 4-6 hours to dry before applying the 2<sup>nd</sup> coat, following the same application method.
- Allow complete drying.
- After 16-24 hours has elapsed, for maximum protection and added durability, **TRIBE Arusha** may be overcoated with 1-2 even coat(s) of **TRIBE Glaze**, using a roller.

## PRECAUTIONS

---

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- Due to the natural components of the product, there may be slight colour variations from batch to batch, which is beyond our control. It is preferable to whenever possible to manufacture the total amount required for each elevation.

---

## **DISCLAIMER**

---

This guide is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.