

TECHNICAL DATA SHEETS

PERMOGLAZE AQUA PRIME

DESCRIPTION	Permoglaze Aqua Prime is a superior quality water-based acrylic opacifying primer, ideal for concrete surfaces, walls and ceilings. Interior and exterior use.		
PURPOSE	Direct application for use as a primer or undercoat to the following non- chalking and non-powdery substrates: new and old plaster, cement, concrete, stone, brickwork, stucco, foamed polystyrene, pebbledash, Tyrolean finish, breeze blocks, wallpaper, building boards, hardboard. This primer has no residual odour and can safely be used in rooms to be occupied the following day. Overcoat with the Permoglaze range of water-based paints.		
CHARACTERISTICS	<ul style="list-style-type: none"> • Outstanding opacity • Enhances the adhesion of the finishing coat • Good alkali resistance • Excellent flow properties • Hard-wearing and long lasting • Fast and easy to apply • No residual odour • Quick drying • Washable • High spreading rate 		
COMPOSITION	An emulsion paint based on a high durability polymeric medium and incorporating high quality pigments specially selected for their performance.		
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be free of dirt, dust, grease, oil and loose paint. • Surfaces infected by mould or algae growth must be treated with Permoglaze Biocidal Wall Wash followed by Permoglaze Fungicidal Treatment. • Leave to dry before applying Permoglaze Aqua Prime. 		
APPLICATION	Method	Brush, Roller, Air-assisted Spray & Airless Spray	
	Thinning	Water	
	Dilution (Brush & Roller)	Porous Substrates	5-10%
		Non- Porous Substrates	5-10%
	Dilution (Airless Spray)	Porous Substrates	10%
		Non- Porous Substrates	10%
	Cleaning	Water	

TECHNICAL DATA SHEETS

PERMOGLAZE AQUA PRIME

PRODUCT INFORMATION	Finish	Smooth and matt finish when dry
	Shades	White
	Spreading Rate	8-10m ² /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	Drying Time	Touch Dry
Hard Dry		1-3 hours at 25°C
PRECAUTIONS	<ul style="list-style-type: none"> The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. It is not recommended to apply Permolaze Aquaprime on chalking and powdery surfaces; instead either the Permolaze Clear Emulsion Binder or the Permolaze Plaster primer must be used. They will enhance the adhesion of the subsequent coating. Do not apply to very cold surfaces, or to Fletton common bricks 	
PACKAGING	Available in 1,5 & 20 litres	
STORAGE	Store in a cool, dry and well-ventilated place.	
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> Handle with care Ensure good ventilation during application. In case of insufficient ventilation during painting, wear suitable respiratory equipment. Avoid contact with skin and eyes. If contact with skin occurs, wash well with soap and water In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. Keep out of reach of children. Do not use empty paint containers for storing foodstuffs. Do not throw paint containers or contents in the waterways or environment. Contains no added Lead/Mercury/Nickel/Cadmium. 	

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.