

TECHNICAL DATA SHEETS

PERMOGLAZE FLEXIBLE ACRYLIC SEALER

DESCRIPTION	<p>Permoglaze Flexible Acrylic Sealer is a versatile transparent sealer for interior and exterior use with both anti-suction properties and alkali resistance. It is also designed for application on powdery or eroded surfaces. This product is the ideal primer on plaster, cement, brickwork, hardboard, building boards and insulation boards. It is recommended as a preparatory coat on new or old surfaces where it is necessary to stop suction or overcome alkali action and where adhesion is questionable.</p>	
CHARACTERISTICS	<ul style="list-style-type: none"> • Good adhesion on all surfaces • Interior and exterior use • Excellent anti-suction properties • Fast and easy to apply • Alkali resistant • Good spreading rate 	
COMPOSITION	<p>Based on an alkali resistant synthetic medium. No lead added.</p>	
SURFACE PREPARATION	<ul style="list-style-type: none"> • Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter. • Surfaces must be free of dirt, dust, grease, oil and loose paint. • Preparation includes bristle brushing down and scraping to remove dirt and loose material. • Remove grease with warm water and detergent solution, then rinse with clean water. • Treat algae or mould infected surfaces with Permoglaze Biocidal Wall Wash followed by Permoglaze Fungicidal Treatment and allow to dry. 	
APPLICATION	Method	<ul style="list-style-type: none"> • Brush or roller application is generally recommended for all surfaces, but is essential on new plaster, brickwork, cement rendering and powdery surfaces. • Spray application is permissible on hardboard, gypsum plaster board, insulating and acoustic fibreboard.
	Thinning	Supplied ready for normal use, but should thinning be considered necessary, use clean, fresh water.
	Cleaning	Wash equipment with clean water immediately after use.
PRODUCT INFORMATION	Finish	Slight sheen
	Shades	Clear
	Spreading Rate/litre	<p>On normal smooth surfaces as below: Hardboard: $\pm 15\text{m}^2$ Insulating & acoustic fibreboards and tiles: $\pm 7\text{m}^2$ Gypsum plasters boards: $\pm 13\text{m}^2$ Plaster, cement, concrete and brickwork: $7\text{-}9\text{m}^2$ The spreading rate will be lower on rough surfaces</p>
	Drying Time	<p>Touch Dry ± 1 hour depending on atmospheric conditions Recoating Time Allow at least ± 2 hours before overcoating with Permoglaze Flexible Acrylic</p>

TECHNICAL DATA SHEETS

PERMOGLAZE FLEXIBLE ACRYLIC SEALER

PRECAUTIONS	The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
PACKAGING	Available in 1, 5 & 20 litres
STORAGE	Keep in a cool, dry and well-ventilated area.
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none">• Handle with care• Ensure good ventilation during application.• In case of insufficient ventilation during painting, wear suitable respiratory equipment.• Avoid contact with skin and eyes.• If contact with skin occurs, wash well with soap and water• In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.• Keep out of reach of children.• Do not use empty paint containers for storing foodstuffs.• Do not throw paint containers or contents in the waterways or environment.• Contains no added Lead/Mercury/Nickel/Cadmium.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.