

TRIBE

TECHNICAL DATA SHEET

TRIBE RODRIGUES

DESCRIPTION

TRIBE RODRIGUES is a low VOC, water-based textured finish which has been formulated with coloured flakes blended in an acrylic system. Tribe Rodrigues has a granulated speckled stone-finish.

TYPE/COMPOSITION

Emulsion paint based on highly durable polymeric medium, incorporating dried flakes.

SUBSTRATE RECOMMENDATION

Recommended for interior surfaces **only**. Not suitable for use on substrates where there is contact with water, such as bathrooms, kitchen sinks and damp walls

SURFACE PREPARATION

- Surface must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.
- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.
- Sanding is recommended for new substrates to remove dirt and cement flashes.

APPLICATION

- It is highly recommended that Tribe Rodrigues be applied by a trained applicator to achieve desired finish and effect.
- Apply one coat of Tribe Fine Primer tinted to the chosen Tribe Rodrigues colour, with a roller to obtain a uniform surface coverage
- Allow Tribe Fine Primer to dry completely before applying Tribe Rodrigues.
- 2 coats of Tribe Rodrigues at the spread rate of 3m²/liter are recommended to achieve desired finish and effect.
- Apply 1st coat of Tribe Rodrigues with roller, and then spread with a clean 6-inch brush. Allow to dry for 7-8 hours.
- Recoat Tribe Rodrigues using same technique as above and allow to dry overnight.

TRIBE

TECHNICAL DATA SHEET

PHYSICAL DATA

Viscosity	120 -130 KU
Specific Gravity	1.17 (± 5%)
pH	8.5-9
Weight Solids Content	46% (± 5%)
Volume Solids Content	30% (± 5%)
Spread Rate	3m ² /liter
Application Temperatures	> 10° C < 35 ° C
Storage Temperatures	> 5° C < 35 ° C
Shelf Life of unopened containers	12 months
Vehicle Type	Pure Acrylic
Cleaning Solvent	Water

SHADES

Refer to Samples at Point of Sales

PRECAUTIONS

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- It is recommended that the surface where products are being applied is not dry during application process, to avoid marks caused by the application tools being used.
- Touch ups are not recommended, apply from corner to corner, or from a natural cut off point to another.
- Do not apply thick layers of Tribe Rodrigues as it will take too long to dry.

THINNING

Not recommended

CLEANING

Wash equipment with clean water immediately after use

TRIBE

TECHNICAL DATA SHEET

PACKAGING

Available in 1 & 5 liters

STORAGE

Store in a cool, dry and well-ventilated place. Storage temperature should be $> 5^{\circ} \text{C} < 35^{\circ} \text{C}$

HEALTH & SAFETY

- Handle with Care.
- Avoid contact with skin and eyes
- If contact with skin occurs, wash well with soap and water.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Use in well-ventilated areas.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- If swallowed, seek medical advice immediately and show this container or label.
- Do not use empty paint containers for storing foodstuffs.

For further information, please contact our Technical Information Service.

Important to Note:

- Considering the nature of this product, its colour can vary slightly from batch to batch and the texture can vary too due to its application technique.
- This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container

Date: 20th April 2017