

FRESCO DI CALCE

ANTIQUE EFFECT FINISH

DECORATIVE PAINTS & COATINGS



COLORTEK®

Description

FRESCO DI CALCE is a decorative paint specifically designed to create deep and pronounced antique effects on interior and exterior walls

Recommended For

Interior & exterior applications on plaster, embossed wall coverings, gypsum board, concrete, cement, brickwork & block work.

Key Features

- Provides life, depth and translucency
- Washable (after full curing)
- UV resistant
- 100% acrylic
- Low VOC
- Long open time
- Non-flammable

Physical Properties

Solvent Type	Waterborne
Gloss at 60°	18 an eggshell finish. Testing based on ASTM D523. Classified according to MPI.
Spreading Rate	Approximately 20 - 25 m ² /kg depending on surface porosity and application technique
Average Dry Time	2 to 4 hours based on ASTM D 1640
Recoat	After 24 hours
Flash Point	Not Applicable
Dry Film Thickness	10 – 20 microns depending on application technique
Thinner	No thinning required
Adhesion	Classified 5B based on ASTM 3359-B for excellent adhesion
Density	1.09 g/cm ³
Volume Solids	15 %
Viscosity	15 000 – 20 000 cP (Spindle 4/Speed 5) based on ASTM D2196
VOC	27 g/L - Compliant with EU 2010 regulations maximum of 30 g/L.
Bases	1600/00-Suolo

Surface Preparation

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean.

New plaster or masonry surfaces must be allowed to cure (28 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Knife off any protrusions and prime the plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. **EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH.** Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces.

FRESCO DI CALCE

ANTIQUÉ EFFECT FINISH

DECORATIVE PAINTS & COATINGS



COLORTEK®

Primer Systems

SURFACE TYPE	RECOMMENDED COLORTEK PRIMER
Drywall	Colortek Primer
Porous masonry	Colortek Sealer, Colortek Primer
Non-porous masonry	Colortek Primer or Colortek Undercoat
Wood	Colortek Undercoat or Wood Primer
Metal	Colortek Adhero, Adhero quick dry, SX47 StopRust, Aquazinc

Application Conditions

Do not apply at temperatures below 5 °C or when rain is expected.

Application Method

Prime the surface with two coats of Fresco primer. Once the surface has completely dried apply, apply Fresco di Calce using the Fresco brush in rotational movements with uneven pressure. A second coat can be applied if desired.

To achieve the metallic effect, apply 1 coat of Metallo by adding 40% Classic Color

Tip: Only dip approximately 1mm of the brush into the paint.

Pack Size

- 1 US Quart – 0.87 kg
- 1 US Gallon – 3.48 kg

Shelf Life

24 months from the date of production.

Storage and Handling

Care should be taken to avoid spillage. Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

Safety

Use under well ventilated conditions. Do not breathe or inhale spray mist or sanding dust. Avoid skin contact; spillage on the skin should immediately be removed with suitable cleanser, soap and water. In case of eye contact, flush immediately with water for at least 15 minutes and seek medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

Cleaning

Remove as much leftover product as possible from the application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses.

Technical Assistance

Available through your local COLORTEK® Design Center or through your COLORTEK PAINTS® authorized distributor. For the location of the retailer nearest you, email us at info@colortek.eu or check our website www.colortek.eu.

Disclaimer

Product batches are subject to stringent quality control checks in conformity with ISO 9001:2008, Certificate CH12/1128.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.