

TRIBE

TECHNICAL DATA SHEET

TRIBE Glaze

DESCRIPTION	TRIBE Glaze , a single component water-based urethane clear glaze that may be used as a protective sealer for the TRIBE coatings.	
CHARACTERISTICS	<ul style="list-style-type: none">• Interior and exterior use for added durability and lower maintenance.• Outstanding interior and exterior durability• Water based, ready to use, very low odour• Fast drying and over-coating properties• Easy to apply, easy to keep clean• Excellent penetration and adhesion properties• Excellent alkali resistance and non-yellowing• Water resistant but still allows the substrate to breathe• Non-toxic and non-irritant	
SURFACE PREPARATION	<ul style="list-style-type: none">• All surfaces must be sound, dry and clean.• Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.	
APPLICATION	Method	Brush or Roller
	Thinning	Ready to use
	<ul style="list-style-type: none">• Ensure that the surface is clean, dry and sound and free of all contaminants such as salt, dirt, dust, etc.• Evenly apply and crosshatch 1 or 2 coats of TRIBE Glaze, using a brush or roller. NB remove excess TRIBE Glaze from the brush or roller to prevent the product causing streaks or milky patches	
PRODUCT INFORMATION	Binder	Urethane Acrylic
	Colour	Clear
	Sheen	Satin
	Spreading Rate	6 – 10 m ² /Lt, depends on the condition and porosity of the substrate and the application method being used.
	VOC	In compliance with world standards of <5g/litre for VOC
	Drying Time	Touch Dry 2 hours at 23 ^o C and 50% humidity
	Over-coating Time	2-4 hours
PRECAUTIONS	All spread rates are approximate and are dependent on substrate type and profile, tools used and loss factor due to weather conditions. Always ensure adequate drying times of the products are adhered to so as not to compromise the product performance. Hot, humid, cold or wet conditions will affect the drying time. The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.	
PACKAGING - BASE	5Lt & 20 Lt	
STORAGE	Store unopened in a cool, dry and well-ventilated place for up to 12 months.	

TRIBE

TECHNICAL DATA SHEET

SAFETY, HEALTH & ENVIRONMENT INFORMATION

- Handle with care
- Ensure good ventilation during application.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- Avoid contact with skin and eyes.
- If contact with skin occurs, wash well with soap and water.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Do not use empty paint containers for storing foodstuffs.
- Do not throw paint containers or contents in the waterways or environment.
- Contains no added **lead / mercury / nickel / cadmium**.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.