

## ZAMBEZI TEXTURE

a low VOC, premium quality water based product with a metallic luster finish.



### APPLY WITH

---

- Brush "4"
- Brush "6"
- Roller



### RECOMMENDED FOR

---

Interior surfaces only. Not suitable for use on substrates where there is contact with water, such as bathtubs, kitchen sinks and damp walls.

# TRIBE

## **SURFACE PREPARATION**

---

- Surface must be dry and moisture content of surface should not be more than 10% when measured with a moisture meter.
- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.
- Sanding is recommended for new substrates to remove dirt and cement flashes.

## **APPLICATION**

---

- It is highly recommended that Tribe Zambezi Texture be applied by a skilled applicator to achieve desired finish and effect.
- Apply 1 coat of Tribe Fine Primer tinted to the selected Tribe Zambezi Texture colour with a roller to obtain a uniform surface coverage.
- Allow Tribe Fine Primer to dry completely before applying the second coat.
- Recoat Tribe Fine Primer with roller and allow complete drying before applying Tribe Zambezi Texture.
- Drying time of Tribe Fine Primer shall depend on weather conditions. Ideally 4 hours would be sufficient.
- 2 coats of Tribe Zambezi Texture at the spread rate of 4m<sup>2</sup>/liter are recommended for a good finish.
- Apply first coat of Tribe Zambezi Texture with roller and create texture using a 6-inch brush.
- Texture can be created by various patterns, either by crisscross strokes or vertical straight lines.
- First coat will require a minimum of 4 hours to dry.
- Recoat Tribe Zambezi Texture using same technique as above and allow to dry overnight.

## **PRECAUTIONS**

---

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- It is recommended that the surface where products are being applied is not dry during application process, to avoid marks caused by the application tools being used.
- Touch ups are not recommended, apply from corner to corner, or from a natural cut off point to another.

## **IMPORTANT TO NOTE**

---

- Considering the nature of this product, its colour can vary slightly from batch to batch.
- Due to the application technique, the texture may also vary.

## **DISCLAIMER**

THIS GUIDE IS BASED ON EXTENSIVE LAB TESTS AND FIELD USE. HOWEVER, IF USED UNDER UNSPECIFIED CONDITIONS AND IF APPLICATION INSTRUCTIONS ARE NOT FOLLOWED CORRECTLY, THE PERFORMANCE OF THE PRODUCT MAY DIFFER.

FOR ANY FURTHER INFORMATION PLEASE REFER TO THE TECHNICAL DATA SHEET OR CONTACT OUR TECHNICAL DEPARTMENT.