

## TECHNICAL DATA SHEETS

### PERMOGLAZE MULTI-TASK

<b>DESCRIPTION</b>	Permoglaze Multi-Task is a water-based high-quality acrylic paint that provides excellent adhesion to various substrates such as galvanized metal substrates, wood, concrete, plaster of Paris, PVC & recycled plastic.	
<b>CHARACTERISTICS</b>	<ul style="list-style-type: none"> <li>• Excellent adhesion to various substrates</li> <li>• UV resistant</li> <li>• Suitable for interior &amp; exterior uses</li> <li>• Good spreading rate</li> </ul>	
<b>COMPOSITION</b>	An emulsion-based paint formulated with a high durability acrylic resin and incorporating the highest quality pigments specially selected for their performance.	
<b>SURFACE PREPARATION</b>	<ul style="list-style-type: none"> <li>• Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.</li> <li>• Surfaces must be free of dirt, dust, grease, oil and loose paint.</li> <li>• Surfaces infected by mould or algae growth must be treated with <b>Permoglaze Biocidal Wall Wash</b>, followed by <b>Permoglaze Fungicidal Treatment</b>.</li> <li>• Powdery, chalky &amp; porous surfaces must be properly sealed with 1 coat of <b>Permoglaze Clear Emulsion Binder</b>.</li> <li>• Galvanised metal substrates must be properly cleaned, then primed with 1 coat of <b>Permoglaze Water- Based Metal Primer</b>.</li> <li>• Internal Wood substrates should be primed with 1 coat of <b>Permoglaze Undercoat</b>.</li> <li>• Leave to dry before applying <b>Permoglaze Multi-Task</b>.</li> <li>• 3 coats are recommended for best performance.</li> </ul>	
<b>APPLICATION</b>	Method	Brush, Roller, Airless Spray
	Thinning	Water
	Dilution	1 <sup>st</sup> Coat Dilution volume ratio of 5 parts of paint to 1 part of water.
		2 <sup>nd</sup> & 3 <sup>rd</sup> Coat Dilution volume ratio of 10 parts of paint to 1 part of water.
	Cleaning	Water
<b>PRODUCT INFORMATION</b>	Finish	Smooth
	Shades	White, pastel, medium & dark
	Volume Solids	36-40 %
	Spreading Rate	+10 m <sup>2</sup> /liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode
	DFT	Dry film thickness will vary between 35 to 45 µm per coat on non-absorbent and smooth substrate.
	VOC	EU Limit for this product (cat A/d) : 130g/l (2010). This product contains maximum 3.0g/l VOC.

## TECHNICAL DATA SHEETS

### PERMOGLAZE MULTI-TASK

	Drying Time	Touch Dry Recoating time	30 minutes at 25°C 1-3 hours at 25°C
<b>RECAUTIONS</b>	<ul style="list-style-type: none"> <li>The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.</li> <li>This product is not recommended to be used on untreated Mild Steel Metal Substrates as rusting may occur.</li> <li>Do not apply to very cold and damp surfaces.</li> <li>Do not over-thin the paint in order not to affect performance.</li> </ul>		
<b>PACKAGING</b>	Available in 1, 5 & 20 litres		
<b>STORAGE</b>	Store in a cool, dry and well-ventilated place.		
<b>SAFETY, HEALTH &amp; ENVIRONMENT INFORMATION</b>	<ul style="list-style-type: none"> <li>Handle with care</li> <li>Ensure good ventilation during application.</li> <li>In case of insufficient ventilation during painting, wear suitable respiratory equipment.</li> <li>Avoid contact with skin and eyes.</li> <li>If contact with skin occurs, wash well with soap and water</li> <li>In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.</li> <li>Keep out of reach of children.</li> <li>Do not use empty paint containers for storing foodstuffs.</li> <li>Do not throw paint containers or contents in the waterways or environment.</li> <li>Contains no added <b>Lead/Mercury/Nickel/Cadmium</b>.</li> </ul>		

For further information, kindly contact our Technical Information Service.

**Note:** This Technical Data Sheet is subject to change without prior notice.

#### DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.