

TECHNICAL DATA SHEETS

PERMOGLAZE ECO+ SOFT FEEL

DESCRIPTION

PERMOGLAZE ECO+ Soft Feel is a superior water-based paint with excellent Class 1 wet scrub resistance according to ISO 11998. It dries to give an even finish with an attractive mid-silk finish. It can be used for decoration and protection and can be applied on interior surfaces.

PERMOGLAZE ECO+ Soft Feel is 99.8% VOC Free* and thus strengthens our commitment to reduce the impact of air quality ** for the building industries.

* Based on in-can VOC content, measured in accordance with ISO 11890-2:2020.

** Independently tested for emissions, including formaldehyde, TVOC, TSVOC and Cat 1A & 1B carcinogens.

CHARACTERISTICS

- Compliant with Indoor Air Comfort – VOC Emission Protocols: **PERMOGLAZE ECO+ Soft Feel** is an A+ Categorized product as per the French VOC Regulation and passes various protocols; French CMR Components, Italian CAM Edilizia, ABG/AgBB, Belgium Regulation.
- Compliant with CDPH - VOC Emission Protocol
- Qualifies for LEED v4 and LEED v4.1 BETA (February 2021) projects
- Ultra-low VOCs
- Odourless
- Ecological
- Highly washable - Achieves a Class 1 wet scrub resistance when tested according to ISO 11998
- Easy to apply
- Quick drying
- Good opacity
- Good flow properties
- High spreading rate
- Hard-wearing and long lasting
- Excellent adhesion even on new plaster
- Excellent colour retention
- Good resistance against UV cement degradation
- Good alkali resistance



TECHNICAL DATA SHEETS

PERMOGLAZE ECO+ SOFT FEEL

COMPOSITION An emulsion-based paint formulated with a high durability acrylic resin and incorporating the highest quality pigments specially selected for their performance.

SURFACE PREPARATION

- Surfaces must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.
- Surfaces must be free of dirt, dust, grease, oil and loose paint.
- Surfaces infected by mould or algae growth must be treated with **PERMOGLAZE Biocidal Wall Wash**, followed by **PERMOGLAZE Fungicidal Treatment**.

Bare and Porous Concrete Surfaces

- Bare and porous concrete surfaces must be cleaned with water and then primed with 1 coat of **PERMOGLAZE Matt Emulsion** for maximum opacity.
- Leave to dry before applying 2 coats of **PERMOGLAZE ECO+ Soft Feel**

Skimmed Porous Surfaces

- 1 coat of **PERMOGLAZE Clear Emulsion Binder** or **PERMOGLAZE Plaster Primer** must be applied on skimmed porous surfaces and then primed with 1 coat of **PERMOGLAZE Matt Emulsion** for maximum opacity.
- Leave to dry before applying 2 coats of **PERMOGLAZE ECO+ Soft Feel**.

APPLICATION	Method	Brush, Roller, Airless Spray	
	Thinning	Water	
	Dilution	1 st Coat	Dilution volume ratio of 5 parts of paint to 1 part of water.
		2 nd & 3 rd Coat	Dilution volume ratio of 10 parts of paint to 1 part of water.
	Cleaning	Water	



TECHNICAL DATA SHEETS

PERMOGLAZE ECO+ SOFT FEEL

PRODUCT INFORMATION	<p>Finish Shades Volume Solids Spreading Rate</p> <p>DFT</p> <p>VOC</p> <p>SVOC</p> <p>Drying Time</p>	<p>Decorative finish with a light surface sheen White, pastel, medium & dark 35% - 40% 8-10m²/liter/coat depending on surface porosity, ambient conditions, colour, dilution and application mode</p> <p>Dry film thickness will vary between 45 to 55 µm per coat on non-absorbent and smooth substrate.</p> <p>Limit for this product: 10g/L. This product contains less than 3.0g/L VOC.</p> <p>Limit for this product: 30-40g/L. This product contains less than 1.0/L VOC.</p> <p>Touch Dry 30 minutes at 25°C Recoating time 1-3 hours at 25°C</p>
PRECAUTIONS	<ul style="list-style-type: none"> The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%. Do not apply to very cold and damp surfaces. 	
PACKAGING	Available in 1, 5 & 20 litres	
STORAGE	Store in a cool, dry and well-ventilated place.	
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none"> Handle with care Ensure good ventilation during application. In case of insufficient ventilation during painting, wear suitable respiratory equipment. Avoid contact with skin and eyes. If contact with skin occurs, wash well with soap and water In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention. Keep out of reach of children. Do not use empty paint containers for storing foodstuffs. Do not throw paint containers or contents in the waterways or environment. Contains no added lead/mercury/nickel/cadmium. 	

Note: This Technical Data Sheet is subject to change without prior notice.

Page 3 of 4

23rd August 2022

Revision 001

Sofap Ltd, DBM Industrial Zone, Coromandel, Mauritius
Tél. : (230) 405 7000 | Fax : (230) 405 7007 | Service Clientèle : 800 1515
Email : sofap@sofap.mu | Website : www.sofap.mu

ISO 9001:2015 Certified | ISO 14001:2015 Certified



TECHNICAL DATA SHEETS

PERMOGLAZE ECO+ SOFT FEEL

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.

